

Sampling Cans

ASTM D4057; ASTM D4306; IP 51; BS 3195 Part 1; ISO 3170

- Cork fitted with metal washers and hook
- Weight enclosed in false bottom
- Heavy gauge wire handle with cable guide
- Perforated thermometer well on double wall

A series of simple and safe to use vessels to take samples from non-pressurised bulk storage without contamination and transferring them to laboratory equipment.

The sample case and fittings are manufactured from either copper, tinned steel, or (for Jet Fuel use) stainless steel. A double wall sample can with a copper inner and a brass outer, equipped with a perforated thermometer well, is available for heated oil samples.



| Single Wall Sampling Cans | | | | | | |
|---------------------------|-----------|-----------------|----------|----------------------|----------------------|---------|
| Seta Part | Capacity | Material | Diameter | Length (inc. handle) | Neck Dia. (internal) | Weight |
| 14710-0 | 500 ml | Cooper | 6.4 cm | 31 cm | 3.8 cm | 1.25 kg |
| 14730-0 | 500 ml | Tinned Steel | 6.4 cm | 32 cm | 3.8 cm | 1.4 kg |
| 14800-0 | 500 ml | Stainless Steel | 6.4 cm | 31 cm | 3.8 cm | 1 kg |
| 14790-0 | 1 litre | Copper | 8.3 cm | 34 cm | 3.8 cm | 2 kg |
| 14700-0 | 1 litre | Copper | 8.3 cm | 35 cm | 3.8 cm | 2.5 kg |
| 14720-0 | 1 litre | Tinned Steel | 8.3 cm | 36 cm | 3.8 cm | 2.4 kg |
| 14801-0 | 1 litre | Stainless Steel | 8.3 cm | 36 cm | 3.8 cm | 2 kg |
| 14750-0 | 1.5 litre | Copper | 8.3 cm | 45 cm | 3.8 cm | 3 kg |
| 14802-0 | 2 litre | Stainless Steel | 8.3 cm | 63 cm | 3.8 cm | 2.5 kg |

| Double Wall Sampling Cans | | | | | | |
|---------------------------|----------|---------------------------|----------|----------------------|----------------------|--------|
| Seta Part | Capacity | Material | Diameter | Length (inc. handle) | Neck Dia. (internal) | Weight |
| 14740-0 | 1 litre | Cooper inner, Brass outer | 8.8 cm | 43 cm | 2.5 cm | 2.7 kg |